



The Colours of Nature

Putty Tivolisse 1

Description of the Product

Tivolisse 1 acrylic based

Name of the Brand

Tivoli Tivolisse White



Famille I Classe 7b 2

- A single layer of Gypsum putty Tivolisse can remove holes and cracks in drywall, walls and ceilings, such as nail holes, scratches etc...
- Gypsum putty Tivolisse may cover more than 3 mm thick supports. [Drying time varies depending on the thickness used.]
- It is favorable to use the coating on healthy carriers and: the floated cements, gypsum board...
- You can paint with any kind of paint.

Interior

- Vertical masonry walls
- Cement or concrete and plaster
- Walls and ceilings

Caution:

Book in direct sunlight and do not expose to temperatures less than 0°C.

Drying time: 10°C	20°C	30°C
8h	6h	4h
Minimum	12h	Maximum
		24

25 Kg
5 Kg
1 Kg

Application Tips:

- Gypsum putty Tivolisse is used without primer
- In case the drywall, ceilings and walls of old paintings, it is preferable to perform a primary for a good surface.
- Avoid application on wet backgrounds.

HEALTH AND SAFETY

Non-flammable, contains antibacterial and fungicides. In case of contact with eyes, rinse thoroughly with water and consult a doctor.

